

TAMAR SEAL 410-SF FOR POWDER APPLICATIONS



24 MONTHS WARRANTY



Food industry




Chemistry industry




Mineral industry

HEAVY DUTY POWDER SEAL


SEAL OPTIONS




Split seal



Bearing integrated



Flexible joint integrated



Air flushed seal



Reliable | Smart | Simple

PARAMETERS

- Max. sealing pressure_____1 bar (14 psi)
- Max. shaft speed_____3 m/s (10 f/s)
- PH_____0-14
- Max Temperture_____200°C (392°F)
- Max radial runout_____0.5mm (0.02")

Consult Tamar for parameters that exceed the range above

Features

MTZ 410-SF is specially designed for **screw conveyors and feeders**. The MTZ 410SF easily fits any screw feeder designs and provides 3-4 weeks notification before maintenance.


- Optional split cartridge - for simple and easy installaion.
- Can be serviced while the equipment is running no downtime.
- Acts as a third bearing to support the shaft and reduces run-outs.
- Average life - 2 years

Patent No: 8,215,643 B2

TAMAR SEAL RANGE




410-SF Screw Conveyors



420-VD Vacuum dryers



430-RV Rotary valves



440-PM Packing machines




450-SP Screw pumps



510-RM Ribbon mixer



610-AG Agitators



620-BL Blowers



710-SP Slurry pumps



720-PP Process pumps



730-TP Turbine pumps



740-PC Progressive cavity pumps

Your local TAMAR distributor:

Klinkenberg
ZAANSTAD B.V.

Noordervaartdijk 3

1561PS Krommenie

Tel: +31 (0) 75 6287855

Email: Info@klinkenbergbv.nl

Web: www.klinkenbergbv.nl

www.tamar-tech.com